

AT-PP □□□ □□□

KT □□□ □□□□ □ PushPull □□□□ / IP65



AT-PP □□□□ KT □□□ □□□ □□□□□ □□□□□ □□□□ □□□□ □□□ □□□□ □□□ □□□□. Pushpu
 AT-PP□□□□ □□□□ □□□ □□□ □□□ □□□□ □□□□ □□□□ □□□ □ □□ □□□□□ □□□ □□□□□ □□□ □ □□
 PushPull □□ □ add-on housing□ □□ □□ □□ □□□.


IP54	IP55	IP64	IP65	RIWA	HL3 EN 45545-2
ECOLAB certified	UV ISO 4892-2A	RoHS compliant	REACH COMPLIANCE	Made in Germany	

IP □□□□ (EN 60529)	IP54, IP55, IP64, IP65
	□□□□□ □□□ □□□□□
	UL94-V0, □□□□□
	-40 C° to 90 C°
	□□□ □□, □□□□□

□□ □ □□

- By utilising the AT-PP grommet, connectors can be integrated directly into the cable entry frame
- □□□ □□□ □□ □□
- □□□□□ □□□
- Grommet is suitable for PushPull housings
- Cost-saving assembly

□□ □□ □ □□

AT-PP	39961
	4251269322570
EAN	5
	42 mm
	41,5 mm
	19 mm
□□ □□	2 mm