

KEL-BES-S split cable gland with brush strips

for cable pass-through, thread sizes M32 / M50



For round metric cut-outs M32/M50 icotek offers the split cable gland with brush strips KEL-BES-S round. It can be either directly snapped into the cut-out or screwed with a locknut, which is included in the shipment.

Split cable glands with brush strips KEL-BES-S are suited for routing cables into server racks, control panels and electrical enclosures. Due to the split frame the KEL-BES-S can also be subsequently installed around the routed cables.

Note: Snap-in mounting possible if wall thickness is 1 - 2.5 mm. For wall thickness < 1 mm and > 2.5 mm, a locknut must be used.



Specifications

Material	Polycarbonate Brushes: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-20 C° to 90 C°
Properties	silicone free, halogen free
Mounting options	Fasten with locknut, Snap-in

Advantages & benefits

- Fast and easy assembly
- Subsequent assembly possible
- Versatile utilisation
- Allows reduced airflow while filtering out dust, hair and larger particulate matter
- Visual screening
- Protects cables against wear due to sharp edges of the cut-out

Product types & sizes

KEL-BES-S 32



Part No.	51538
EAN	4251269318702
PU	10
Mounting height	10 mm
External diameter	46 mm
Cut-out size, metric	M32
Thread	M32 x 1,5

Thread length	20 mm
For min. wall thickness	1 mm
For max. wall thickness	2,5 mm

KEL-BES-S 50



Part No.	51540
EAN	4251269318306
PU	10
Mounting height	10 mm
External diameter	62,5 mm
Cut-out size, metric	M50
Thread	M50 x 1,5

Thread length	20 mm
For min. wall thickness	1 mm
For max. wall thickness	2,5 mm

