

KEL-DPZ multi-membrane cable entry plates, round

with metric threads M25 - M63 / IP66 / IP68 / UL Type 12/4X




KEL-DPZ round cable entry plates are designed to route and seal cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The assembly of the KEL-DPZ round with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ round provides strain relief and protection IP66 / IP68 / UL Type 4X.

The round versions of the KEL-DPZ series have a thread to fit in metric cut-outs from M25 to M63. Thus cut-outs for metric cable glands can be used.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.



Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
UL Type (UL 50E)	UL Type 12, UL Type 4X
Material	Elastomer Base frame: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Fasten with locknut

Advantages & benefits

- Fast mounting
- High cable density
- Certified protection IP66/IP68 (acc. to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric cut-outs
- Hexagonal locknut included in the delivery
- Hygienic design - free of dirt-collecting recesses

Product types & sizes

KEL-DPZ 25|3 gy




Part No.	43736	Mounting height	8 mm
EAN	4251269320439	Cut-out size, round	25,3 mm
PU	10	Cut-out size, metric	M25
For max. no. of cables	3	Thread	M25 x 1,5
Colour	grau (ähnlich RAL 7035)	Thread length	14 mm
Height	22 mm	Clamping range	2 x 3.2 - 5.2 mm
External diameter	39 mm		1 x 3.2 - 6.5 mm

KEL-DPZ 25|3 bk


Part No. **50736**
 EAN **4251269320453**
 PU **10**
 For max. no. of cables **3**
 Colour **schwarz**
 Height **22 mm**
 External diameter **39 mm**

Mounting height **8 mm**
 Cut-out size, round **25,3 mm**
 Cut-out size, metric **M25**
 Thread **M25 x 1,5**
 Thread length **14 mm**
 Clamping range **2 x 3.2 - 5.2 mm**
1 x 3.2 - 6.5 mm

KEL-DPZ 25|4 gy


Part No. **43737**
 EAN **4251269320446**
 PU **10**
 For max. no. of cables **4**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **39 mm**

Mounting height **8 mm**
 Cut-out size, round **25,3 mm**
 Cut-out size, metric **M25**
 Thread **M25 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 5.2 mm**

KEL-DPZ 25|4 bk

Part No. **50737**
 EAN **4251269320460**
 PU **10**
 For max. no. of cables **4**
 Colour **schwarz**
 Height **22 mm**
 External diameter **39 mm**

Mounting height **8 mm**
 Cut-out size, round **25,3 mm**
 Cut-out size, metric **M25**
 Thread **M25 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 5.2 mm**

KEL-DPZ 32|4 gy


Part No. **43732**
 EAN **4251269310539**
 PU **10**
 For max. no. of cables **4**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **14 mm**
 Clamping range **3 x 3.2 - 6.5 mm**
1 x 7.2 - 12.5 mm

KEL-DPZ 32|4 bk

Part No. **50732**
 EAN **4251269315152**
 PU **10**
 For max. no. of cables **4**
 Colour **schwarz**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **14 mm**
 Clamping range **3 x 3.2 - 6.5 mm**
1 x 7.2 - 12.5 mm

KEL-DPZ 32|4-2 gy


Part No. **43733**
 EAN **4251269310546**
 PU **10**
 For max. no. of cables **4**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 5 - 9.5 mm**

KEL-DPZ 32|4-2 bk

Part No. **50733**
 EAN **4251269315169**
 PU **10**
 For max. no. of cables **4**
 Colour **schwarz**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 5 - 9.5 mm**

KEL-DPZ 32|7 gy


Part No. **43734**
 EAN **4251269310553**
 PU **10**
 For max. no. of cables **7**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ 32|7 bk

Part No. **50734**
 EAN **4251269315176**
 PU **10**
 For max. no. of cables **7**
 Colour **schwarz**
 Height **22 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32,3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ 40|8 gy

Part No. **43741**
 EAN **4251269310577**
 PU **10**
 For max. no. of cables **8**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **52 mm**

Mounting height **8 mm**
 Cut-out size, round **40,4 mm**
 Cut-out size, metric **M40**
 Thread **M40 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ 40|8 bk

Part No. **50741**
 EAN **4251269315190**
 PU **10**
 For max. no. of cables **8**
 Colour **schwarz**
 Height **22 mm**
 External diameter **52 mm**

Mounting height **8 mm**
 Cut-out size, round **40,4 mm**
 Cut-out size, metric **M40**
 Thread **M40 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ 50|8 gy

Part No. **43750**
 EAN **4251269310584**
 PU **10**
 For max. no. of cables **8**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **14 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm

KEL-DPZ 50|8 bk

Part No. **50750**
 EAN **4251269315206**
 PU **10**
 For max. no. of cables **8**
 Colour **schwarz**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **14 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm

KEL-DPZ 50|10 gy


Part No. **43751**
 EAN **4251269310591**
 PU **10**
 For max. no. of cables **10**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm

KEL-DPZ 50|10 bk

Part No. **50751**
 EAN **4251269315213**
 PU **10**
 For max. no. of cables **10**
 Colour **schwarz**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm

KEL-DPZ 50|12 gy


Part No. **43752**
 EAN **4251269310607**
 PU **10**
 For max. no. of cables **12**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
8 x 5 - 10.2 mm

KEL-DPZ 50|12 bk


Part No. **50752**
 EAN **4251269315220**
 PU **10**
 For max. no. of cables **12**
 Colour **schwarz**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**

KEL-DPZ 50|19 gy


Part No. **43758**
 EAN **4251269310621**
 PU **10**
 For max. no. of cables **19**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **14 mm**
 Clamping range **19 x 3.2 - 6.5 mm**

KEL-DPZ 50|19 bk


Part No. **50758**
 EAN **4251269315244**
 PU **10**
 For max. no. of cables **19**
 Colour **schwarz**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **19 x 3.2 - 6.5 mm**

KEL-DPZ 50|78 gy


Part No. **43756**
 EAN **4251269310614**
 PU **10**
 For max. no. of cables **78**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **76 x 1.5 - 2.6 mm**
2 x 2.5 - 5 mm

KEL-DPZ 50|78 bk

Part No. **50756**
 EAN **4251269315237**
 PU **10**
 For max. no. of cables **78**
 Colour **schwarz**
 Height **22 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50,4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **76 x 1.5 - 2.6 mm**
2 x 2.5 - 5 mm

KEL-DPZ 63|9 gy


Part No. **43760**
 EAN **4251269310638**
 PU **10**
 For max. no. of cables **9**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm

KEL-DPZ 63|9 bk

Part No. **50760**
 EAN **4251269315251**
 PU **10**
 For max. no. of cables **9**
 Colour **schwarz**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm

KEL-DPZ 63|13 gy

Part No. **43761**
 EAN **4251269310645**
 PU **10**
 For max. no. of cables **13**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

KEL-DPZ 63|13 bk

Part No. **50761**
 EAN **4251269315268**
 PU **10**
 For max. no. of cables **13**
 Colour **schwarz**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

KEL-DPZ 63|14 gy


Part No. **43762**
 EAN **4251269310652**
 PU **10**
 For max. no. of cables **14**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **14 x 5 - 10.2 mm**

KEL-DPZ 63|14 bk


Part No. **50762**
 EAN **4251269315275**
 PU **10**
 For max. no. of cables **14**
 Colour **schwarz**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **14 x 5 - 10.2 mm**

KEL-DPZ 63|35 gy

Part No. **43763**
 EAN **4251269310669**
 PU **10**
 For max. no. of cables **35**
 Colour **grau (ähnlich RAL 7035)**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **35 x 3.2 - 6.5 mm**

KEL-DPZ 63|35 bk

Part No. **50763**
 EAN **4251269315282**
 PU **10**
 For max. no. of cables **35**
 Colour **schwarz**
 Height **22 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63,4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **14 mm**
 Clamping range **35 x 3.2 - 6.5 mm**