

# KEL-JUMBO split cable entry frames

for cables with diameters of up to 65 mm / IP54 / UL Type 12



The KEL-JUMBO cable entry system for installation of cables and conduits with a diameter of up to 65 mm, especially suited for supply cables. The innovative grommet design with the flex-membrane provides flexing and adjustment of the position for larger and more rigid cables.

We recommend round cut-outs, which can be made using standard knockout tools. Suggested cut-out: cable diameter +15 - 20%.

A flat rubber gasket is included in the shipment.

IP54

UL TYPE  
12

C<sub>UL</sub> US

RIIA

HL3  
EN 45545-2

EN 61373

ECOLAB  
certified

UV  
ISO 4892-2A

RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

## Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, UV-resistant, silicone free, anti-corrosive (V2A versions), halogen free
Mounting options	Screw type mounting
Mounting height	35 mm

## Advantages & benefits

- Installation of cables up to 65 mm in diameter
- It is possible to install rigid cables at angles
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Strain relief according to EN 62444


## Product types & sizes

### KEL-JUMBO 1



Part No.	42360
EAN	4251269308550
PU	1
For max. no. of cables	1
Max. cable diameter	65 mm
Length	110 mm
Width	116 mm

Height	35 mm
Mounting height	35 mm
No. of screw holes	4
Diam. of screw holes	7 mm
Screw material	Stahl, galvanisch verzinkt
Suitable for grommets	1 x KTF

**KEL-JUMBO 1 V2A**

Part No. **42360.200**  
 EAN **4251269308567**  
 PU **1**  
 For max. no. of cables **1**  
 Max. cable diameter **65 mm**  
 Length **110 mm**  
 Width **116 mm**

Height **35 mm**  
 Mounting height **35 mm**  
 No. of screw holes **4**  
 Diam. of screw holes **7 mm**  
 Screw material **Edelstahl V2A**  
 Suitable for grommets **1 x KTF**

**KEL-JUMBO 2**

Part No. **42350**  
 EAN **4251269308536**  
 PU **1**  
 For max. no. of cables **2**  
 Max. cable diameter **65 mm**  
 Length **200 mm**  
 Width **116 mm**

Height **35 mm**  
 Mounting height **35 mm**  
 No. of screw holes **4**  
 Diam. of screw holes **7 mm**  
 Screw material **Stahl, galvanisch verzinkt**  
 Suitable for grommets **2 x KTF**

**KEL-JUMBO 2 V2A**

Part No. **42350.200**  
 EAN **4251269308543**  
 PU **1**  
 For max. no. of cables **2**  
 Max. cable diameter **65 mm**  
 Length **200 mm**  
 Width **116 mm**

Height **35 mm**  
 Mounting height **35 mm**  
 No. of screw holes **4**  
 Diam. of screw holes **7 mm**  
 Screw material **Edelstahl V2A**  
 Suitable for grommets **2 x KTF**