

SF|ZL strain relief plates

pluggable on 35 mm top hat rails



The strain relief plate SF|ZL is used for assembly on 35 mm top hat DIN rails. It can be used for strain relief of cables and conduits.

The SF|ZL range is based upon the strain relief plate ZL, which is mounted on snap-in mounting feet for 35 mm top hat rails.



Specifications

Material	Polyamide Snap foot: Spring steel
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	silicone free, halogen free
Mounting options	Snap-in

Advantages & benefits

- Strain relief according to EN 62444
- Fast and easy mounting
- Cost-effective solution
- High cable density
- Versatile utilisation

Product types & sizes

SF ZL 39	Part No.	32351	Mounting height	11,4 mm
	EAN	4251269301247	No. of teeth	3
	PU	10		
	For max. no. of cables	3		
	Length	38,5 mm		
	Width	51,7 mm		
	Height	16 mm		
SF ZL 60	Part No.	32352	Mounting height	11,4 mm
	EAN	4251269301254	No. of teeth	4
	PU	10		
	For max. no. of cables	4		
	Length	59,5 mm		
	Width	51,7 mm		
	Height	16 mm		

SF ZL 70 	Part No.	32353	Mounting height	11,4 mm
	EAN	4251269301261	No. of teeth	5
	PU	10		
	For max. no. of cables	5		
	Length	69,1 mm		
	Width	51,7 mm		
	Height	16 mm		
SF ZL 87 	Part No.	32354	Mounting height	11,4 mm
	EAN	4251269301278	No. of teeth	6
	PU	10		
	For max. no. of cables	6		
	Length	86,5 mm		
	Width	51,7 mm		
	Height	16 mm		
SF ZL 103 	Part No.	32355	Mounting height	11,4 mm
	EAN	4251269301285	No. of teeth	7
	PU	10		
	For max. no. of cables	7		
	Length	102,5 mm		
	Width	51,7 mm		
	Height	16 mm		
SF ZL 121 	Part No.	32356	Mounting height	11,4 mm
	EAN	4251269301292	No. of teeth	8
	PU	10		
	For max. no. of cables	8		
	Length	121 mm		
	Width	51,7 mm		
	Height	16 mm		
SF ZL 140 	Part No.	32357	Mounting height	11,4 mm
	EAN	4251269301308	No. of teeth	9
	PU	10		
	For max. no. of cables	9		
	Length	139,5 mm		
	Width	51,7 mm		
	Height	16 mm		
SF ZL 180 	Part No.	32358	Mounting height	11,4 mm
	EAN	4251269301315	No. of teeth	12
	PU	10		
	For max. no. of cables	12		
	Length	180 mm		
	Width	51,7 mm		
	Height	16 mm		

