

KEL-QTE round pluggable cable entry plates

for cables with connectors, tool-free assembly / IP54



The KEL-QTE easily routes pre-terminated cables, multi-conductors, hoses or conduits without using any tools for assembly.

The KEL-QTE fits on cut-outs of 20 mm in diameter.

IP54



ECOLAB certified



RoHS compliant



Made in Germany

Specifications

| | |
|-----------------------|---|
| IP rating (EN 60529) | IP54 |
| Material | Elastomer |
| Flame class | UL94-V0, self-extinguishing |
| Operating temperature | -40 C° to 100 C° |
| Properties | UV-resistant, silicone free, halogen free |
| Mounting options | Snap-in |
| Mounting height | 2 mm |

Advantages & Benefits

- Quick assembly without tools
- Routing of cables with and without connectors
- Upon disassembly (e.g. maintenance) screwing and unscrewing of the cable entry frame is not necessary
- Suitable for metric cut-outs

Product types & Sizes

KEL-QTE 20|2.5



| | |
|-------------------------------------|---------------|
| Part No. | 43412 |
| EAN | 4251269309793 |
| PU | 10 |
| For max. no. of cables | 2 |
| Max. cable diam., with connector | 3,2 mm |
| Max. cable diam., without connector | 5,2 mm |
| Height | 6 mm |
| Mounting height | 2 mm |
| For min. wall thickness | 1,5 mm |
| For max. wall thickness | 2,5 mm |
| Min. cable diam., with connector | 2,6 mm |
| Min. cable diam., without connector | 1 mm |

KEL-QTE 20/3

| | |
|-------------------------------------|----------------------|
| Part No. | 43413 |
| EAN | 4251269309809 |
| PU | 10 |
| For max. no. of cables | 2 |
| Max. cable diam., with connector | 3,8 mm |
| Max. cable diam., without connector | 5,2 mm |
| Height | 6 mm |
| Mounting height | 2 mm |
| For min. wall thickness | 1,5 mm |
| For max. wall thickness | 2,5 mm |
| Min. cable diam., with connector | 3,1 mm |
| Min. cable diam., without connector | 1 mm |

KEL-QTE 20/4

| | |
|-------------------------------------|----------------------|
| Part No. | 43414 |
| EAN | 4251269309816 |
| PU | 10 |
| For max. no. of cables | 2 |
| Max. cable diam., with connector | 4,8 mm |
| Max. cable diam., without connector | 5,2 mm |
| Height | 6 mm |
| Mounting height | 2 mm |
| For min. wall thickness | 1,5 mm |
| For max. wall thickness | 2,5 mm |
| Min. cable diam., with connector | 3,8 mm |
| Min. cable diam., without connector | 1 mm |

KEL-QTE 20/5

| | |
|-------------------------------------|----------------------|
| Part No. | 43415 |
| EAN | 4251269309823 |
| PU | 10 |
| For max. no. of cables | 2 |
| Max. cable diam., with connector | 5,6 mm |
| Max. cable diam., without connector | 5,2 mm |
| Height | 6 mm |
| Mounting height | 2 mm |
| For min. wall thickness | 1,5 mm |
| For max. wall thickness | 2,5 mm |
| Min. cable diam., with connector | 4,7 mm |
| Min. cable diam., without connector | 1 mm |