

KEL-SCDP multi-range cable entry grommets

pluggable, for single cables with diameters up to 36 mm / IP65



With the KEL-SCDP cable entry grommet, single cables, hoses, and conduits can be routed and sealed at a rating of IP65. Its unique advantage is the large sealing range.

The single circular membrane can be peeled away to accommodate the specific diameter of the cable or hose. For this purpose, only a small hole between the rings needs to be pierced. Then the corresponding ring can be removed. The peeled-off area is always round, ensuring a secure seal around cable/hose.

Another advantage is the high mounting flexibility. The KEL-SCDP can simply be plugged into cut-outs with wall thicknesses from 1.5 to 4.0 mm.

The version KEL-SCDP-RW is approved for the use in the railway technology in accordance with EN45545-2 HL3.

IP54

HL3
EN 45545-2

RoHS
compliant

IP55

EN 61373

REACH
COMPLIANCE

IP64

ECOLAB
certified

Made in
Germany

IP65

ISO 4892-2A

Specifications


IP rating (EN 60529)	IP54, IP55, IP64, IP65
Material	Elastomer
Operating temperature	-40 C° to 80 C°
Properties	halogen free, silicone free
Mounting options	Snap-in

Advantages & Benefits

- Perfect edge protection and sealing (IP65)
- Circular membranes can be peeled off easily
- Quick assembly without tools

Product types & Sizes


KEL-SCDP 25



Part No.	43480
EAN	4251269320811
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	32 mm
Mounting height	11 mm

Cut-out size, round	25,3 mm
Cut-out size, metric	M25
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 5 - 16 mm

KEL-SCDP-RW 25



Part No.	43490
EAN	4251269320859
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	32 mm
Mounting height	11 mm

Cut-out size, round	25,3 mm
Cut-out size, metric	M25
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 5 - 16 mm

KEL-SCDP 32

Part No.	43481
EAN	4251269320828
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	39 mm
Mounting height	11 mm

Cut-out size, round	32,3 mm
Cut-out size, metric	M32
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 5 - 22 mm

KEL-SCDP-RW 32

Part No.	43491
EAN	4251269320866
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	39 mm
Mounting height	11 mm

Cut-out size, round	32,3 mm
Cut-out size, metric	M32
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 5 - 22 mm

KEL-SCDP 40

Part No.	43482
EAN	4251269320835
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	47 mm
Mounting height	11 mm

Cut-out size, round	40,4 mm
Cut-out size, metric	M40
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 8 - 28 mm

KEL-SCDP-RW 40

Part No.	43492
EAN	4251269320873
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	47 mm
Mounting height	11 mm

Cut-out size, round	40,4 mm
Cut-out size, metric	M40
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 8 - 28 mm

KEL-SCDP 50

Part No.	43483
EAN	4251269320842
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	57 mm
Mounting height	11 mm

Cut-out size, round	50,4 mm
Cut-out size, metric	M50
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 8 - 36 mm

KEL-SCDP-RW 50

Part No.	43493
EAN	4251269320880
PU	10
For max. no. of cables	1
Height	11 mm
External diameter	57 mm
Mounting height	11 mm

Cut-out size, round	50,4 mm
Cut-out size, metric	M50
For min. wall thickness	1,5 mm
For max. wall thickness	4 mm
Clamping range	1 x 8 - 36 mm

