

SF|ZL strain relief plates

pluggable on 35 mm top hat rails



The strain relief plate SF|ZL is used for assembly on 35 mm top hat DIN rails. It can be used for strain relief of cables and conduits.

The SF|ZL range is based upon the strain relief plate ZL, which is mounted on snap-in mounting feet for 35 mm top hat rails.



Specifications

Material	Polyamide Snap foot: Spring steel
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	silicone free, halogen free
Mounting options	Snap-in

Advantages & Benefits

- Strain relief according to EN 62444
- Fast and easy mounting
- Cost-effective solution
- High cable density
- Versatile utilisation

Product types & Sizes

SF|ZL 39



Part No.	32351
EAN	4251269301247
PU	10
For max. no. of cables	3
Length	38,5 mm
Width	51,7 mm
Height	16 mm

Mounting height	11,4 mm
No. of teeth	3

SF|ZL 60



Part No.	32352
EAN	4251269301254
PU	10
For max. no. of cables	4
Length	59,5 mm
Width	51,7 mm
Height	16 mm

Mounting height	11,4 mm
No. of teeth	4

SF|ZL 70

Part No. **32353**
 EAN **4251269301261**
 PU **10**
 For max. no. of cables **5**
 Length **69,1 mm**
 Width **51,7 mm**
 Height **16 mm**

Mounting height **11,4 mm**
 No. of teeth **5**

SF|ZL 87

Part No. **32354**
 EAN **4251269301278**
 PU **10**
 For max. no. of cables **6**
 Length **86,5 mm**
 Width **51,7 mm**
 Height **16 mm**

Mounting height **11,4 mm**
 No. of teeth **6**

SF|ZL 103

Part No. **32355**
 EAN **4251269301285**
 PU **10**
 For max. no. of cables **7**
 Length **102,5 mm**
 Width **51,7 mm**
 Height **16 mm**

Mounting height **11,4 mm**
 No. of teeth **7**

SF|ZL 121

Part No. **32356**
 EAN **4251269301292**
 PU **10**
 For max. no. of cables **8**
 Length **121 mm**
 Width **51,7 mm**
 Height **16 mm**

Mounting height **11,4 mm**
 No. of teeth **8**

SF|ZL 140

Part No. **32357**
 EAN **4251269301308**
 PU **10**
 For max. no. of cables **9**
 Length **139,5 mm**
 Width **51,7 mm**
 Height **16 mm**

Mounting height **11,4 mm**
 No. of teeth **9**

SF|ZL 180

Part No. **32358**
 EAN **4251269301315**
 PU **10**
 For max. no. of cables **12**
 Length **180 mm**
 Width **51,7 mm**
 Height **16 mm**

Mounting height **11,4 mm**
 No. of teeth **12**

