

# CONFIX™ WST split cable protection conduits

for cables with connectors



RoHS  
compliant

REACH  
COMPLIANCE

Made in  
Germany

The CONFIX™ WST is a two piece corrugated conduit. Perfect for routing cables with or without connectors in rough environments.

In conjunction with e.g. [KVT-W90](#), a high degree of flexibility is achieved. Numerous conduit sizes can be used thanks to the wide variety of [split grommets](#) offered.

The length of the CONFIX™ WST split corrugated conduit can be customized to your application.

## Defining your individual length:

Order numbers (ex.):

Length = 1.500 mm --> Order No. 31200.01500

**All conduits are available by the metre (0.5 m steps).**

## Specifications

<b>Material</b>	Polypropylene
<b>Operating temperature</b>	-40 C° to 105 C°
<b>Properties</b>	UV-resistant

## Advantages & benefits

■ Retrofits, repairs and maintenance can be done much more easily and quickly

## Product types & sizes

CONFIX™ WST NW 10



Part No.	<b>31200.xxxxx</b>
EAN	
Package quantity	<b>1</b>
Nominal size	<b>NW 10</b>
External diameter	<b>13,6 mm</b>
Internal diameter	<b>8,7 mm</b>
Bending radius (static)	<b>25 mm</b>

**CONFIX™ WST NW 14**



Part No. **31210.xxxxx** Compatible **31410,**  
EAN with CONFiX™ **31411**  
Package **1** FWS  
quantity  
Nominal size **NW 14**  
External **18,5 mm**  
diameter  
Internal **12,5 mm**  
diameter  
Bending radius **35 mm**  
(static)

**CONFIX™ WST NW 16**



Part No. **31215.xxxxx** Compatible **31413,**  
EAN with CONFiX™ **31414**  
Package **1** FWS  
quantity  
Nominal size **NW 16**  
External **21,5 mm**  
diameter  
Internal **16 mm**  
diameter  
Bending radius **40 mm**  
(static)

CONFIX™ WST NW 20

Part No. **31220.xxxxx**  
EAN  
Package **1**  
quantity  
Nominal size **NW 20**  
External diameter **25,5 mm**  
Internal diameter **19,5 mm**  
Bending radius **45 mm**  
(static)



CONFIX™ WST NW 23

Part No. **31230.xxxxx** Compatible with CONFIX™ **31416,**  
EAN **31417**  
Package **1** FWS  
quantity  
Nominal size **NW 23**  
External diameter **31 mm**  
Internal diameter **24,2 mm**  
Bending radius **50 mm**  
(static)



**CONFiX™ WST NW 29**



Part No. **31235.xxxxx** Compatible **31419,**  
EAN with CONFiX™ **31420**  
Package **1** FWS  
quantity  
Nominal size **NW 29**  
External **35,5 mm**  
diameter  
Internal **27,3 mm**  
diameter  
Bending radius **90 mm**  
(static)

**CONFiX™ WST NW 37**



Part No. **31240.xxxxx** Compatible **31422,**  
EAN with CONFiX™ **31423**  
Package **1** FWS  
quantity  
Nominal size **NW 37**  
External **41,4 mm**  
diameter  
Internal **31 mm**  
diameter  
Bending radius **110 mm**  
(static)

**CONFIX™ WST NW 45**

Part No. **31250.xxxxx** Compatible with CONFIX™ **31425, 31426**  
EAN  
Package quantity **1** FWS  
Nominal size **NW 45**  
External diameter **54 mm**  
Internal diameter **42,7 mm**  
Bending radius **130 mm**  
(static)



**CONFIX™ WST NW 70**

Part No. **31260.xxxxx**  
EAN  
Package quantity **1**  
Nominal size **NW 70**  
External diameter **79,8 mm**  
Internal diameter **66,5 mm**  
Bending radius **190 mm**  
(static)



