

KEL-DPZ-HD hygienic multi-membrane cable entry plates, round

with metric threads M25 - M63 / IP66 / IP68, FDA compliant



The new cable entry plates KEL-DPZ-HD with metric thread from M25 to M63 have been developed for installation in food processing and packaging machines.

During the development according to the Hygienic Design guidelines, care was taken to ensure that the visible side of the cable entry plate are free of dirt-collecting recesses. The surface was kept very smooth ($Ra = 0,421 \mu m$ acc. to ISO 4287). The outer contour has a radius of 6 mm instead of the required 3 mm. In addition, the KEL-DPZ-HD uses an FDA-compliant elastomer in accordance with food approval 1935/2004/EG and (EU) 10/2011. The signal colour blue ensures a clear visual colour recognition.

The cable entry plates are designed to route several cables and hoses with a diameter range of 3.2 mm to 22.2 mm and seal them acc. to IP65/66/67/68. A significant advantage over cable glands is the significantly higher cable density and the flexibility of the cable diameter range. The fixation is very simple with the locknut.




Specifications

IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
Material	Elastomer Base frame: Polyamide
Flame class	UL94-HB
Operating temperature	-40 C° to 80 C°
Properties	silicone free, halogen free, resistant to oil and mould, higher chemical resistance


Advantages & benefits

- Elastomer of the cable entry plate made of material according to 1935/2004/EG, (EU) 10/2011
- FDA compliant
- Developed according to hygienic design guidelines (EHEDG)
- Hygienic design - free of dirt-collecting recesses
- Ecolab certified
- Very flat design
- Very smooth surface ($Ra = 0,421 \mu m$ acc. to ISO 4287)
- Very fast assembly
- Cable diameter 3,2 - 22,2 mm
- Very large sealing areas and clamping areas
- High cable density
- Dual sealing of cables (IP66/IP68)
- Suitable for metric cut-outs
- Reproducible cleaning process
- Very low moisture absorption
- High resistance to aromatic solvents, oils, greases, mineral products
- No corrosion possible because plastics have been processed
- Maintenance free
- Hexagonal locknut included in the delivery


Product types & sizes

KEL-DPZ-HD 25|3


Part No.	70345	Colour	blue (similar RAL 5005)
EAN	4251269336935	External diameter	39 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	3	Cut-out size, metric	M25
Max. cable diameter	6,5 mm	Cut-out size, round	25,3 mm
Height	22 mm	Thread	M25 × 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	2 x 3.2 - 5.2 mm 1 x 3.2 - 6.5 mm

KEL-DPZ-HD 25|4


Part No.	70346	Colour	blue (similar RAL 5005)
EAN	4251269336942	External diameter	39 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	4	Cut-out size, metric	M25
Max. cable diameter	5,2 mm	Cut-out size, round	25,3 mm
Height	22 mm	Thread	M25 × 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	4 x 3.2 - 5.2 mm

KEL-DPZ-HD 32|4


Part No.	70351	Colour	blue (similar RAL 5005)
EAN	4251269322785	External diameter	44 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	12,5 mm	Cut-out size, round	32,3 mm
Height	22 mm	Thread	M32 × 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	3 x 3.2 - 6.5 mm 1 x 7.2 - 12.5 mm

KEL-DPZ-HD 32|4-2

Part No.	70352	Colour	blue (similar RAL 5005)
EAN	4251269322792	External diameter	44 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	4	Cut-out size, metric	M32
Max. cable diameter	9,5 mm	Cut-out size, round	32,3 mm
Height	22 mm	Thread	M32 × 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	4 x 5 - 9.5 mm


KEL-DPZ-HD 32|7

Part No.	70353	Colour	blue (similar RAL 5005)
EAN	4251269322808	External diameter	44 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	7	Cut-out size, metric	M32
Max. cable diameter	6,5 mm	Cut-out size, round	32,3 mm
Height	22 mm	Thread	M32 × 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	7 x 3.2 - 6.5 mm

KEL-DPZ-HD 40|8


Part No. **70354**
 EAN **4251269322815**
 Package quantity **5**
 For max. no. of cables **8**
 Max. cable diameter **10,2 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **52 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M40**
 Cut-out size, round **40,4 mm**
 Thread **M40 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ-HD 50|8


Part No. **70355**
 EAN **4251269322822**
 Package quantity **5**
 For max. no. of cables **8**
 Max. cable diameter **12,5 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **62 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M50**
 Cut-out size, round **50,4 mm**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm

KEL-DPZ-HD 50|10


Part No. **70356**
 EAN **4251269322839**
 Package quantity **5**
 For max. no. of cables **10**
 Max. cable diameter **22,2 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **62 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M50**
 Cut-out size, round **50,4 mm**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **7 x 3.2 - 6.5 mm**
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm

KEL-DPZ-HD 50|12


Part No. **70357**
 EAN **4251269322846**
 Package quantity **5**
 For max. no. of cables **12**
 Max. cable diameter **10,2 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **62 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M50**
 Cut-out size, round **50,4 mm**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
8 x 5 - 10.2 mm

KEL-DPZ-HD 50|19


Part No. **70358**
 EAN **4251269322853**
 Package quantity **5**
 For max. no. of cables **19**
 Max. cable diameter **6,5 mm**
 Height **22 mm**
 Mounting height **8 mm**

Colour **blue (similar RAL 5005)**
 External diameter **62 mm**
 Surface roughness (ISO 4287) **Ra = 0,421 µm**
 Cut-out size, metric **M50**
 Cut-out size, round **50,4 mm**
 Thread **M50 × 1,5**
 Thread length **14 mm**
 Clamping range **19 x 3.2 - 6.5 mm**




Part No.	70359	Colour	blue (similar RAL 5005)
EAN	4251269322860	External diameter	75 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	9	Cut-out size, metric	M63
Max. cable diameter	22,2 mm	Cut-out size, round	63,4 mm
Height	22 mm	Thread	M63 x 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	1 x 3.2 - 6.5 mm
			3 x 5 - 10.2 mm
			4 x 9 - 16.2 mm
			1 x 16 - 22.2 mm

KEL-DPZ-HD 63|13




Part No.	70360	Colour	blue (similar RAL 5005)
EAN	4251269322877	External diameter	75 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	13	Cut-out size, metric	M63
Max. cable diameter	16,2 mm	Cut-out size, round	63,4 mm
Height	22 mm	Thread	M63 x 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	4 x 3.2 - 6.5 mm
			4 x 5 - 10.2 mm
			5 x 9 - 16.2 mm

KEL-DPZ-HD 63|14



Part No.	70361	Colour	blue (similar RAL 5005)
EAN	4251269322884	External diameter	75 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	14	Cut-out size, metric	M63
Max. cable diameter	10,2 mm	Cut-out size, round	63,4 mm
Height	22 mm	Thread	M63 x 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	14 x 5 - 10.2 mm

KEL-DPZ-HD 63|35



Part No.	70362	Colour	blue (similar RAL 5005)
EAN	4251269322891	External diameter	75 mm
Package quantity	5	Surface roughness (ISO 4287)	Ra = 0,421 µm
For max. no. of cables	35	Cut-out size, metric	M63
Max. cable diameter	6,5 mm	Cut-out size, round	63,4 mm
Height	22 mm	Thread	M63 x 1,5
Mounting height	8 mm	Thread length	14 mm
		Clamping range	35 x 3.2 - 6.5 mm