KEL-FA | Split multi cable entry frames

for cables with connectors, tool-free assembly / IP54 / UL Type 12 $\,$



The KEL-FA range is a compact system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising KT series <u>grommets</u>. After populating the entry frame with grommets and cables, the cover is put on and the two clamping levers are locked with the lower part by pressing them down. The twist-proof construction of the KEL-FA enables intuitive assembly. Routing and sealing with IP54 / UL Type 12 for cable diameters from 1 to 35 mm.

The KEL-FA frames match exactly the cut-out dimensions for 10-, 16- and 24-pin standard industrial connectors. These KEL-FA frames can either be screw mounted or simply snapped into the <u>KEL-SNAP frame</u>.

Specifications

	IP54	Integrated sealing
IP rating (EN 60529)		Quick assembly without tools
UL Type (UL 50E)	UL Type 12	Strain relief according to EN 62444 (when using KT single hole gror
Material	Polyamide	Very high cable density with multi-hole grommets
Flame class	UL94-V0, self-extinguishing	High flexibility with multi-range grommets and the IMAS-CONNECT
Operating temperature	-40 C° to 140 C°	Warranty on pre-terminated cables remains
Properties	UV-resistant, silicone free, anti- corrosive, halogen free	Retrofits, repairs and maintenance can be done much more easily a Wide variety
Mounting options	Screw type mounting,Snap-in with KEL-SNAP	

Product types & sizes

KEL-FA 24|10

				r
ho				1
ho	L	 	 	Ľ

Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets

Advantages & benefits

22 mm 22 mm 112 × 36 mm 4 6 mm 10 x KT small

KEL-FA 24|7



Part No. EAN Package quantity For max. no. of cables Max. cable diameter Length Width

Height Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm 112 × 36 mm 4 6 mm 6 x KT small 1 x KT large

VE	I E	A 7	24 4



icotek

smart cable management