

KEL | Centrally split cable entry frames

for cables with connectors / IP54 / UL Type 12





IP54



UL TYPE 12



UL US



DNV



RoHS compliant



HL3 EN 45545-2



ECOLAB certified



ISO 4892-2A



Made in Germany



REACH COMPLIANCE

The classic KEL is a centrally split cable entry system for routing cables with connectors, providing an IP54 / up to UL Type 12 rating.

The slit [KT grommet](#) matching the cable diameter is placed around the cable and inserted into the cable entry frame. The split cable entry frames KEL match exactly the cut-out dimensions of 10-, 16- and 24-pin standard industrial connectors. Either a cut-out of 36 mm or 46 mm in height can be chosen depending on the cables being routed. The size KEL-B matches the cut-out dimensions of 46 x 46 mm measuring instruments.

Based on the frame sizes KEL 16 and KEL 24, there are also extended versions with additional middle frames available. Thus allowing a quick, easy and cost effective routing solution for up to 120 cables or hoses.

For tool-free assembly / disassembly of the cable entry frames the [snap mounting frame KEL-SNAP](#) can be used.

A flat rubber gasket is included in the shipment.

This product is available in different versions: With steel screws or stainless steel screws. It is also possible to integrate threaded bushings. Please ask us about your desired variant.

The version with threaded bushings enables the cable entry frame to be screwed onto the housing from the inside out. This protects against vandalism and tampering with the housing from the outside.


Specifications

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	vibration proof, silicone free, anti-corrosive (V2A versions), halogen free, UV-resistant
Mounting options	Screw type mounting,Snap-in with KEL-SNAP
Mounting height	17 mm

Advantages & benefits

- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Strain relief according to EN 62444
- High stability, vibration resistant
- Space-saving shape
- Greatly increased cable density when using double or quadruple grommets

Product types & sizes


KEL 24 10		Part No.	42241	Height	17 mm
		EAN	4251269308277	Mounting height	17 mm
		Package quantity	10	Cut-out size	112 x 36 mm
		For max. no. of cables	40	No. of screw holes	4
		Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
		Length	147 mm	Screw material	Mild steel, galvanically zinc plated
		Width	58 mm	Min. cable diam., with connector	
				Suitable for grommets	10 x KT small

KEL 24|10 V2A




Part No.	42241.200	Height	17 mm
EAN	4251269308284	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	40	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	10 x KT small

KEL 24|7




Part No.	42247	Height	17 mm
EAN	4251269308314	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	25	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	6 x KT small 1 x KT large

KEL 24|7 V2A



Part No.	42247.200	Height	17 mm
EAN	4251269308321	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	25	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	6 x KT small 1 x KT large

KEL 24|5




Part No.	42248	Height	17 mm
EAN	4251269308338	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	20	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	5 x KT small

KEL 24|5 V2A




Part No.	42248.200	Height	17 mm
EAN	4251269308345	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	20	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	5 x KT small

KEL 24|4




Part No.	42244	Height	17 mm
EAN	4251269308291	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	10	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm		
		Min. cable diam., with connector	
		Suitable for grommets	2 x KT small 2 x KT large

KEL 24|4 V2A




Part No.	42244.200	Height	17 mm
EAN	4251269308307	Mounting height	17 mm
Package quantity	10	Cut-out size	112 × 36 mm
For max. no. of cables	10	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	2 x KT small 2 x KT large

KEL 24|15-E




Part No.	42209	Height	17 mm
EAN	4251269308017	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	60	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	83 mm		
		Min. cable diam., with connector	
		Suitable for grommets	15 x KT small

KEL 24|15-E V2A





Part No.	42209.200	Height	17 mm
EAN	4251269308024	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	60	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	83 mm	Min. cable diam., with connector	
		Suitable for grommets	15 x KT small


KEL 24|12-E





Part No.	42208	Height	17 mm
EAN	4251269307997	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 66 mm
For max. no. of cables	45	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	83 mm		
		Min. cable diam., with connector	
		Suitable for grommets	11 x KT small 1 x KT large

KEL 24 12-E V2A	Part No.	42208.200	Height	17 mm
	EAN	4251269308000	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 66 mm
	For max. no. of cables	45	No. of screw holes	4
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Stainless steel (V2A)
	Width	83 mm	Min. cable diam., with connector	
			Suitable for grommets	11 x KT small
				1 x KT large


KEL 24 10-E	Part No.	49056	Height	17 mm
	EAN	4251269312212	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 66 mm
	For max. no. of cables	39	No. of screw holes	4
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Mild steel, galvanically zinc plated
	Width	83 mm	Min. cable diam., with connector	
			Suitable for grommets	10 x KT small

KEL 24 10-E V2A	Part No.	49056.200	Height	17 mm
	EAN	4251269312229	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 66 mm
	For max. no. of cables	40	No. of screw holes	4
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Stainless steel (V2A)
	Width	83 mm	Min. cable diam., with connector	
			Suitable for grommets	10 x KT small

KEL 24 9-E	Part No.	42207	Height	17 mm
	EAN	4251269307973	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 66 mm
	For max. no. of cables	30	No. of screw holes	4
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Mild steel, galvanically zinc plated
	Width	83 mm	Min. cable diam., with connector	
			Suitable for grommets	7 x KT small
				2 x KT large


KEL 24 9-E V2A	Part No.	42207.200	Height	17 mm
	EAN	4251269307980	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 66 mm
	For max. no. of cables	30	No. of screw holes	4
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Stainless steel (V2A)
	Width	83 mm	Min. cable diam., with connector	
			Suitable for grommets	7 x KT small
				2 x KT large

KEL 24|20-MT




Part No.	42232	Height	17 mm
EAN	4251269308215	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	80	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	
		Suitable for grommets	20 x KT small

KEL 24|20-MT V2A




Part No.	42232.200	Height	17 mm
EAN	4251269308222	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	80	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	102 mm	Min. cable diam., with connector	
		Suitable for grommets	20 x KT small

KEL 24|17-MT




Part No.	42224	Height	17 mm
EAN	4251269308130	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	65	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	
		Suitable for grommets	16 x KT small 1 x KT large

KEL 24|17-MT V2A





Part No.	42224.200	Height	17 mm
EAN	4251269308147	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	65	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	102 mm	Min. cable diam., with connector	
		Suitable for grommets	16 x KT small 1 x KT large


KEL 24|14-MT





Part No.	42225	Height	17 mm
EAN	4251269308154	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 82 mm
For max. no. of cables	50	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	
		Suitable for grommets	12 x KT small 2 x KT large

KEL 24 14-MT V2A 	Part No.	42225.200	Height	17 mm
	EAN	4251269308161	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 82 mm
	For max. no. of cables	48	No. of screw holes	6
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Stainless steel (V2A)
	Width	102 mm	Min. cable diam., with connector Suitable for grommets	12 x KT small 2 x KT large


KEL 24 11-MT 	Part No.	42222	Height	17 mm
	EAN	4251269308093	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 82 mm
	For max. no. of cables	35	No. of screw holes	6
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Mild steel, galvanically zinc plated
	Width	102 mm	Min. cable diam., with connector Suitable for grommets	8 x KT small 3 x KT large

KEL 24 11-MT V2A 	Part No.	42222.200	Height	17 mm
	EAN	4251269308109	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 82 mm
	For max. no. of cables	35	No. of screw holes	6
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Stainless steel (V2A)
	Width	102 mm	Min. cable diam., with connector Suitable for grommets	8 x KT small 3 x KT large

KEL 24 8-MT 	Part No.	42221	Height	17 mm
	EAN	4251269308079	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 82 mm
	For max. no. of cables	20	No. of screw holes	6
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Mild steel, galvanically zinc plated
	Width	102 mm	Min. cable diam., with connector Suitable for grommets	4 x KT small 4 x KT large


KEL 24 8-MT V2A 	Part No.	42221.200	Height	17 mm
	EAN	4251269308086	Mounting height	17 mm
	Package quantity	1	Cut-out size	112 × 82 mm
	For max. no. of cables	20	No. of screw holes	6
	Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
	Length	147 mm	Screw material	Stainless steel (V2A)
	Width	102 mm	Min. cable diam., with connector Suitable for grommets	4 x KT small 4 x KT large

KEL 24|30-2MT




Part No.	42234	Height	17 mm
EAN	4251269308253	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	120	No. of screw holes	8
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	30 x KT small

KEL 24|30-2MT V2A




Part No.	42234.200	Height	17 mm
EAN	4251269308260	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	120	No. of screw holes	8
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	30 x KT small

KEL 24|27-2MT




Part No.	42233	Height	17 mm
EAN	4251269308239	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	105	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	26 x KT small 1 x KT large

KEL 24|27-2MT V2A




Part No.	42233.200	Height	17 mm
EAN	4251269308246	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	105	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	26 x KT small 1 x KT large

KEL 24|24-2MT




Part No.	42227	Height	17 mm
EAN	4251269308192	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	90	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	22 x KT small 2 x KT large

KEL 24|24-2MT V2A




Part No.	42227.200	Height	17 mm
EAN	4251269308208	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	90	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	22 x KT small 2 x KT large

KEL 24|21-2MT




Part No.	42226	Height	17 mm
EAN	4251269308178	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	75	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	18 x KT small 3 x KT large

KEL 24|21-2MT V2A




Part No.	42226.200	Height	17 mm
EAN	4251269308185	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	75	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	18 x KT small 3 x KT large

KEL 24|12-2MT




Part No.	42223	Height	17 mm
EAN	4251269308116	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	30	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Mild steel, galvanically zinc plated
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	6 x KT small 6 x KT large

KEL 24|12-2MT V2A




Part No.	42223.200	Height	17 mm
EAN	4251269308123	Mounting height	17 mm
Package quantity	1	Cut-out size	112 × 126 mm
For max. no. of cables	30	No. of screw holes	8
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	147 mm	Screw material	Stainless steel (V2A)
Width	146 mm	Min. cable diam., with connector	
		Suitable for grommets	6 x KT small 6 x KT large

KEL 16|8




Part No.	42168	Height	17 mm
EAN	4251269307911	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	32	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	8 x KT small

KEL 16|8 V2A




Part No.	42168.200	Height	17 mm
EAN	4251269307928	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	30	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	8 x KT small

KEL 16|5



Part No.	42165	Height	17 mm
EAN	4251269307898	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	17	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	4 x KT small 1 x KT large

KEL 16|5 V2A




Part No.	42165.200	Height	17 mm
EAN	4251269307904	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	17	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	4 x KT small 1 x KT large

KEL 16|4




Part No.	42164	Height	17 mm
EAN	4251269307874	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	4 x KT small

KEL 16|4 V2A




Part No.	42164.200	Height	17 mm
EAN	4251269307881	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	4 x KT small

KEL 16|2




Part No.	42162	Height	17 mm
EAN	4251269307850	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	2	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	2 x KT large

KEL 16|2 V2A




Part No.	42162.200	Height	17 mm
EAN	4251269307867	Mounting height	17 mm
Package quantity	10	Cut-out size	86 × 36 mm
For max. no. of cables	2	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	
		Suitable for grommets	2 x KT large

KEL 16|12-E




Part No.	42141	Height	17 mm
EAN	4251269307713	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	48	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	84 mm	Min. cable diam., with connector	
		Suitable for grommets	12 x KT small

KEL 16|12-E V2A



Part No.	42141.200	Height	17 mm
EAN	4251269307720	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	48	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	84 mm	Min. cable diam., with connector	
		Suitable for grommets	12 x KT small

KEL 16|6-E




Part No.	42140	Height	17 mm
EAN	4251269307690	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	18	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	84 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	2 x KT large

KEL 16|6-E V2A




Part No.	42140.200	Height	17 mm
EAN	4251269307706	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 66 mm
For max. no. of cables	18	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	84 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	2 x KT large

KEL 16|16-MT




Part No.	42145	Height	17 mm
EAN	4251269307775	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 82 mm
For max. no. of cables	64	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	16 x KT small
		Suitable for grommets	

KEL 16|16-MT V2A




Part No.	42145.200	Height	17 mm
EAN	4251269307782	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 82 mm
For max. no. of cables	61	No. of screw holes	6
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Stainless steel (V2A)
Width	102 mm	Min. cable diam., with connector	16 x KT small
		Suitable for grommets	

KEL 16|10-MT



Part No.	42144	Height	17 mm
EAN	4251269307751	Mounting height	17 mm
Package quantity	1	Cut-out size	86 × 82 mm
For max. no. of cables	34	No. of screw holes	6
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	120 mm	Screw material	Mild steel, galvanically zinc plated
Width	102 mm	Min. cable diam., with connector	8 x KT small
		Suitable for grommets	2 x KT large

KEL 16|10-MT V2A




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42144.200
4251269307768
1
34
35 mm
120 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
86 × 82 mm
6
5,8 mm
Stainless steel (V2A)
8 x KT small
2 x KT large

KEL 16|4-MT




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42143
4251269307737
1
4
35 mm
120 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
86 × 82 mm
6
5,8 mm
Mild steel, galvanically zinc plated
4 x KT large

KEL 16|4-MT V2A




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42143.200
4251269307744
1
4
35 mm
120 mm
102 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
86 × 82 mm
6
5,8 mm
Stainless steel (V2A)
4 x KT large

KEL 16|24-2MT




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42149
4251269307836
1
96
17 mm
120 mm
146 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
86 × 126 mm
8
5,8 mm
Mild steel, galvanically zinc plated
24 x KT small

KEL 16|24-2MT V2A




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42149.200
4251269307843
1
96
17 mm
120 mm
146 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
86 × 126 mm
8
5,8 mm
Stainless steel (V2A)
24 x KT small

KEL 16|12-2MT




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

42148
4251269307812
1
36
35 mm
120 mm
146 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material
Min. cable diam., with connector
Suitable for grommets

17 mm
17 mm
86 × 126 mm
8
5,8 mm
Mild steel, galvanically zinc plated
8 x KT small
4 x KT large


KEL 16|12-2MT V2A



Part No.	42148.200
EAN	4251269307829
Package quantity	1
For max. no. of cables	36
Max. cable diameter	35 mm
Length	120 mm
Width	146 mm

Height	17 mm
Mounting height	17 mm
Cut-out size	86 × 126 mm
No. of screw holes	8
Diam. of screw holes	5,8 mm
Screw material	Stainless steel (V2A)
Min. cable diam., with connector	8 x KT small
Suitable for grommets	2 x KT large


KEL 16|6-2MT



Part No.	42147
EAN	4251269307799
Package quantity	1
For max. no. of cables	6
Max. cable diameter	35 mm
Length	120 mm
Width	146 mm

Height	17 mm
Mounting height	17 mm
Cut-out size	86 × 126 mm
No. of screw holes	8
Diam. of screw holes	5,8 mm
Screw material	Mild steel, galvanically zinc plated
Min. cable diam., with connector	6 x KT large
Suitable for grommets	


KEL 16|6-2MT V2A



Part No.	42147.200
EAN	4251269307805
Package quantity	1
For max. no. of cables	6
Max. cable diameter	35 mm
Length	120 mm
Width	146 mm

Height	17 mm
Mounting height	17 mm
Cut-out size	86 × 126 mm
No. of screw holes	8
Diam. of screw holes	5,8 mm
Screw material	Stainless steel (V2A)
Min. cable diam., with connector	6 x KT large
Suitable for grommets	


KEL 10|6



Part No.	42216
EAN	4251269308055
Package quantity	10
For max. no. of cables	24
Max. cable diameter	17 mm
Length	98 mm
Width	58 mm

Height	17 mm
Mounting height	17 mm
Cut-out size	65 × 36 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm
Screw material	Mild steel, galvanically zinc plated
Min. cable diam., with connector	6 x KT small
Suitable for grommets	


KEL 10|6 V2A



Part No.	42216.200
EAN	4251269308062
Package quantity	10
For max. no. of cables	24
Max. cable diameter	17 mm
Length	98 mm
Width	58 mm


Height	17 mm
Mounting height	17 mm
Cut-out size	65 × 36 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm
Screw material	Stainless steel (V2A)
Min. cable diam., with connector	6 x KT small
Suitable for grommets	

KEL 10|3




Part No.	42212	Height	17 mm
EAN	4251269308031	Mounting height	17 mm
Package quantity	10	Cut-out size	65 × 36 mm
For max. no. of cables	9	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	98 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	2 x KT small
		Suitable for grommets	1 x KT large

KEL 10|3 V2A




Part No.	42212.200	Height	17 mm
EAN	4251269308048	Mounting height	17 mm
Package quantity	10	Cut-out size	65 × 36 mm
For max. no. of cables	9	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	98 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	2 x KT small
		Suitable for grommets	1 x KT large

KEL-B4




Part No.	42204	Height	17 mm
EAN	4251269307935	Mounting height	17 mm
Package quantity	10	Cut-out size	46 × 46 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	72 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	

KEL-B4 V2A




Part No.	42204.200	Height	17 mm
EAN	4251269307942	Mounting height	17 mm
Package quantity	10	Cut-out size	46 × 46 mm
For max. no. of cables	16	No. of screw holes	4
Max. cable diameter	17 mm	Diam. of screw holes	5,8 mm
Length	72 mm	Screw material	Stainless steel (V2A)
Width	58 mm	Min. cable diam., with connector	4 x KT small
		Suitable for grommets	

KEL-B1



Part No.	42206	Height	17 mm
EAN	4251269307959	Mounting height	17 mm
Package quantity	10	Cut-out size	46 × 46 mm
For max. no. of cables	1	No. of screw holes	4
Max. cable diameter	35 mm	Diam. of screw holes	5,8 mm
Length	72 mm	Screw material	Mild steel, galvanically zinc plated
Width	58 mm	Min. cable diam., with connector	1 x KT large
		Suitable for grommets	

KEL-B1 V2A



Part No.	42206.200
EAN	4251269307966
Package quantity	10
For max. no. of cables	1
Max. cable diameter	35 mm
Length	72 mm
Width	58 mm

Height	17 mm
Mounting height	17 mm
Cut-out size	46 x 46 mm
No. of screw holes	4
Diam. of screw holes	5,8 mm
Screw material	Stainless steel (V2A)
Min. cable diam., with connector	
Suitable for grommets	1 x KT large

