

# KT-DPF | Multi-range cable grommets, black

in pyramid shape, for cable diameters 3-26 mm / IP54



The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

**Black KT-DPF grommets have an increased chemical resistance, e.g. against aggressive oils, coolants etc.**

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

It is recommended that additional strain relief be provided for the cables using a cable tie.

**Cutting of KT-DPF grommets:** Cable diameter less 20%.

IP54



ECOLAB certified



RoHS compliant



Made in Germany


## Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-HB
Operating temperature	-30 C° to 90 C°
Properties	higher chemical resistance


## Advantages & benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

## Product types & sizes

 IP54	Part No.	<b>41360</b>	Height	<b>50 mm</b>
	EAN	<b>4251269307102</b>	Mounting height	<b>33 mm</b>
	Package quantity	<b>10</b>	attr.Klemmbereich kombiniert	<b>3 - 12 mm</b>
	For max. no. of cables	<b>1</b>	Clamping range	<b>1 x 3 - 12 mm</b>
	Colour	<b>black</b>		
	Length	<b>21 mm</b>		
	Width	<b>21 mm</b>		

 IP54	Part No.	<b>41361</b>	Height	<b>59 mm</b>
	EAN	<b>4251269307119</b>	Mounting height	<b>42 mm</b>
	Package quantity	<b>10</b>	For cable type	<b>Round cable</b>
	For max. no. of cables	<b>1</b>	attr.Klemmbereich kombiniert	<b>4 - 18 mm</b>
	Colour	<b>black</b>	Clamping range	<b>1 x 4 - 18 mm</b>
	Length	<b>41,5 mm</b>		
	Width	<b>42 mm</b>		



Part No.  
EAN  
Package quantity  
For max. no. of cables  
Colour  
Length  
Width

**41362**  
**4251269307126**  
**10**  
**1**  
**black**  
**41,5 mm**  
**42 mm**

Height  
Mounting height  
For cable type  
attr.Klemmbereich kombiniert  
Clamping range

**59 mm**  
**42 mm**  
**Round cable**  
**14 - 26 mm**  
**1 x 14 - 26 mm**