

KT-DPF | Multi-range cable grommets, black

in pyramid shape, for cable diameters 3-26 mm / IP54



IP54



ECOLAB
certified



RoHS
compliant



Made in
Germany

The KT-DPF grommets accept a wide range of cable diameters. A great benefit when the exact cable diameter is not known in advance. Due to the flexibility and unique pyramid shape, routing and flexible positioning of rigid cables is much easier compared to using conventional cable glands.

The KT-DPF grommets are not split and therefore only usable for cables without connectors.

Cutting of KT-DPF grommets: Cable diameter less 20%. It is recommended that additional strain relief be provided for the cables using a cable tie.

Specifications


IP rating (EN 60529)	IP54
Material	Elastomer
Flame class	UL94-HB
Operating temperature	-30 C° to 90 C°
Properties	higher chemical resistance

Advantages & benefits

- Large clamping range of 3 to 26 mm with only 3 grommets
- Ideal for wiring non pre-terminated cables locally
- Easy storage

Product types & sizes


KT-DPF-A bk



Part No.	41360
EAN	4251269307102
Package quantity	10
For max. no. of cables	1
Colour	black
Length	21 mm
Width	21 mm


Height	50 mm
Mounting height	33 mm
Clamping range	1 x 3 - 12 mm

KT-DPF-B bk



Part No.	41361
EAN	4251269307119
Package quantity	10
For max. no. of cables	1
Colour	black
Length	41,5 mm
Width	42 mm

Height	59 mm
Mounting height	42 mm
For cable type	Round cable
Clamping range	1 x 4 - 18 mm



Part No.	41362	Height	59 mm
EAN	4251269307126	Mounting height	42 mm
Package quantity	10	For cable type	Round cable
For max. no. of cables	1	Clamping range	1 x 14 - 26 mm
Colour	black		
Length	41,5 mm		
Width	42 mm		