


KEL-DPZ-HD CR hygienic multi-membrane cable entry plates, round

for the use in cleanrooms, M32 - M63 / IP66 / IP68, FDA compliant



The new cable entry plates KEL-DPZ-HD CR with metric thread from M32 to M63 have been developed for installation in food processing and packaging machines as well as for cleanroom applications.

During the development according to the Hygienic Design guidelines, care was taken to ensure that the visible side of the cable entry plate are free of dirt-collecting recesses. The surface was kept very smooth. The outer contour has a radius of 6 mm instead of the required 3 mm. In addition, the KEL-DPZ-HD CR uses an FDA-compliant elastomer in accordance with food approval 1935/2004/EG and (EU) 10/2011. The signal colour blue ensures a clear visual colour recognition.

The cable entry plates are designed to route several cables and hoses with a diameter range of 3.2 mm to 22.2 mm and seal them acc. to IP65/66/67/68. A significant advantage over cable glands is the significantly higher cable density and the flexibility of the cable diameter range. The fixation is very simple with the locknut.

The products with article ending .600 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1. The materials used for these products have been tested and certified for outgassing according to VOC/SVOC (ISO 14644-8; ISO 16000-6,-9,-11,-25, VDI 2083 sheet 17).

The products with the article ending .601 are tested and certified for particle emission for cleanroom class 1 according to ISO 14644-1.

Specifications


IP rating (EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
Material	Elastomer Base frame: Polyamide
Flame class	
Operating temperature	-40 C° to 80 C°
Properties	silicone free, halogen free, resistant to oil and mold, higher chemical resistance

Advantages & Benefits

- Elastomer of the cable entry plate made of material according to 1935/2004/EG, (EU) 10/2011
- FDA compliant
- Developed according to hygienic design guidelines (EHEDG)
- Hygienic design - free of dirt-collecting recesses
- Ecolab certified
- Very flat design
- Very smooth surface
- Very fast assembly
- Cable diameter 3,2 - 22,2 mm
- Very large sealing areas and clamping areas
- High cable density
- Dual sealing of cables (IP66/IP68)
- Suitable for metric cut-outs
- Reproducible cleaning process
- Very low moisture absorption
- High resistance to aromatic solvents, oils, greases, mineral products
- No corrosion possible because plastics have been processed
- Maintenance free

Product Types & Sizes


KEL-DPZ-HD 32|4 CR



Part No. **70351.601**
EAN **4251269328657**
Package quantity **5**
For max. no. of cables **4**
Max. cable diameter **12,5 mm**
Color **blue (similar RAL 5005)**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
Surface roughness (ISO 4287) **Ra = 0,421 µm**
(S)VOC tested **nein**
Clamping range **3 x 3.2 - 6.5 mm**
1 x 7.2 - 12.5 mm


KEL-DPZ-HD 32|4 CR (S)VOC



Part No. **70351.600**
EAN **4251269328534**
Package quantity **5**
For max. no. of cables **4**
Max. cable diameter **12,5 mm**
Color **blue (similar RAL 5005)**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
Surface roughness (ISO 4287) **Ra = 0,421 µm**
(S)VOC tested **ja**
Clamping range **3 x 3.2 - 6.5 mm**
1 x 7.2 - 12.5 mm


KEL-DPZ-HD 32|4-2 CR



Part No. **70352.601**
EAN **4251269328664**
Package quantity **5**
For max. no. of cables **4**
Max. cable diameter **9,5 mm**
Color **blue (similar RAL 5005)**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
Surface roughness (ISO 4287) **Ra = 0,421 µm**
(S)VOC tested **nein**
Clamping range **4 x 5 - 9.5 mm**


KEL-DPZ-HD 32|4-2 CR (S)VOC



Part No. **70352.600**
EAN **4251269328541**
Package quantity **5**
For max. no. of cables **4**
Max. cable diameter **9,5 mm**
Color **blue (similar RAL 5005)**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
Surface roughness (ISO 4287) **Ra = 0,421 µm**
(S)VOC tested **ja**
Clamping range **4 x 5 - 9.5 mm**


KEL-DPZ-HD 32|7 CR



Part No. **70353.601**
EAN **4251269328671**
Package quantity **5**
For max. no. of cables **7**
Max. cable diameter **6,5 mm**
Color **blue (similar RAL 5005)**
Height **22 mm**

Mounting height **8 mm**
External diameter **44 mm**
Cut-out size, round **32,3 mm**
Cut-out size, metric **M32**
Thread **M32 × 1,5**
Thread length **14 mm**
Surface roughness (ISO 4287) **Ra = 0,421 µm**
(S)VOC tested **nein**
Clamping range **7 x 3.2 - 6.5 mm**

**KEL-DPZ-HD 32|7 CR
(S)VOC**




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70353.600
4251269328558
5
7
6,5 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
44 mm
32,3 mm
M32
M32 × 1,5
14 mm
Ra = 0,421 µm
ja
7 x 3.2 - 6.5 mm

KEL-DPZ-HD 40|8 CR




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70354.601
4251269328688
5
8
10,2 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
52 mm
40,4 mm
M40
M40 × 1,5
14 mm
Ra = 0,421 µm
nein
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm

**KEL-DPZ-HD 40|8 CR
(S)VOC**




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70354.600
4251269328565
5
8
10,2 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
52 mm
40,4 mm
M40
M40 × 1,5
14 mm
Ra = 0,421 µm
ja
4 x 3.2 - 6.5 mm
4 x 5 - 10.2 mm

KEL-DPZ-HD 50|8 CR




Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70355.601
4251269328695
5
8
12,5 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm
nein
5 x 5 - 10.2 mm
3 x 7.2 - 12.5 mm

**KEL-DPZ-HD 50|8 CR
(S)VOC**













Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height


70355.600
4251269328572
5
8
12,5 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
62 mm
50,4 mm
M50
M50 × 1,5
14 mm
Ra = 0,421 µm
ja
5 x 5 - 10.2 mm
3 x 7.2 - 12.5 mm

KEL-DPZ-HD 50 10 CR 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70356.601 4251269328701 5 10 22,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 14 mm Ra = 0,421 µm nein 7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm
KEL-DPZ-HD 50 10 CR (S)VOC 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70356.600 4251269328589 5 10 22,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 14 mm Ra = 0,421 µm ja 7 x 3.2 - 6.5 mm 2 x 5 - 10.2 mm 1 x 16 - 22.2 mm
KEL-DPZ-HD 50 12 CR 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70357.601 4251269328718 5 12 10,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 14 mm Ra = 0,421 µm nein 4 x 3.2 - 6.5 mm 8 x 5 - 10.2 mm
KEL-DPZ-HD 50 12 CR (S)VOC 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70357.600 4251269328596 5 12 10,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 14 mm Ra = 0,421 µm ja 4 x 3.2 - 6.5 mm 8 x 5 - 10.2 mm
KEL-DPZ-HD 50 19 CR 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70358.601 4251269328725 5 19 6,5 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 14 mm Ra = 0,421 µm nein 19 x 3.2 - 6.5 mm

KEL-DPZ-HD 50 19 CR (S)VOC 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70358.600 4251269328602 5 19 6,5 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 62 mm 50,4 mm M50 M50 × 1,5 14 mm Ra = 0,421 µm ja 19 x 3.2 - 6.5 mm
KEL-DPZ-HD 63 9 CR 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70359.601 4251269328732 5 9 22,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 75 mm 63,4 mm M63 M63 × 1,5 14 mm Ra = 0,421 µm nein 1 x 3.2 - 6.5 mm 3 x 5 - 10.2 mm 4 x 9 - 16.2 mm 1 x 16 - 22.2 mm
KEL-DPZ-HD 63 9 CR (S)VOC 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70359.600 4251269328619 5 9 22,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 75 mm 63,4 mm M63 M63 × 1,5 14 mm Ra = 0,421 µm ja 1 x 3.2 - 6.5 mm 3 x 5 - 10.2 mm 4 x 9 - 16.2 mm 1 x 16 - 22.2 mm
KEL-DPZ-HD 63 13 CR 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70360.601 4251269328749 5 13 16,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 75 mm 63,4 mm M63 M63 × 1,5 14 mm Ra = 0,421 µm nein 4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 5 x 9 - 16.2 mm
KEL-DPZ-HD 63 13 CR (S)VOC 	Part No. EAN Package quantity For max. no. of cables Max. cable diameter Color Height	70360.600 4251269328626 5 13 16,2 mm blue (similar RAL 5005) 22 mm	Mounting height External diameter Cut-out size, round Cut-out size, metric Thread Thread length Surface roughness (ISO 4287) (S)VOC tested Clamping range	8 mm 75 mm 63,4 mm M63 M63 × 1,5 14 mm Ra = 0,421 µm ja 4 x 3.2 - 6.5 mm 4 x 5 - 10.2 mm 5 x 9 - 16.2 mm


KEL-DPZ-HD 63|14 CR

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70361.601
4251269328756
5
14
10,2 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
Ra = 0,421 µm
nein
14 x 5 - 10.2 mm


**KEL-DPZ-HD 63|14 CR
(S)VOC**

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70361.600
4251269328633
5
14
10,2 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
Ra = 0,421 µm
ja
14 x 5 - 10.2 mm


KEL-DPZ-HD 63|35 CR

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70362.601
4251269328763
5
35
6,5 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
Ra = 0,421 µm
nein
35 x 3.2 - 6.5 mm

**KEL-DPZ-HD 63|35 CR
(S)VOC**

Part No.
EAN
Package quantity
For max. no. of cables
Max. cable diameter
Color
Height

70362.600
4251269328640
5
35
6,5 mm
blue (similar RAL 5005)
22 mm

Mounting height
External diameter
Cut-out size, round
Cut-out size, metric
Thread
Thread length
Surface roughness (ISO 4287)
(S)VOC tested
Clamping range

8 mm
75 mm
63,4 mm
M63
M63 × 1,5
14 mm
Ra = 0,421 µm
ja
35 x 3.2 - 6.5 mm