

QTMB | QUICK (QUICK)

14 - 29 mm / IP54



QTMB QUICK

3mm

IP54

HL3
EN 45545-2

ECOLAB
certified

UV
ISO 4892-2A

PNEUMATICS

RoHS
compliant

REACH
COMPLIANCE


Made in
Germany


Features


- Quick connection
- 7-pin connection for 14 - 29 mm
- UL94-V0, flame retardant
- RoHS compliant

IP (EN 60529)	IP54
	UL94-V0, flame retardant
	-40 C° to 100 C°
	RoHS compliant

Dimensions

QTBG	EAN	42545 4251269321634	2 mm
		10 (RAL 7035)	1
		40 mm	
		39 mm	
		17 mm	

QTMB 14-17	EAN	42515 4251269321603	17 mm
		10	2 mm
		1	
		(RAL 7035)	
		40 mm	
		39 mm	
			1 x 14 - 17 mm

QTMB 16-19


EAN

□□□ □

42516
4251269321986
10
1
 □□(RAL 7035□ □□)
40 mm
39 mm

□□ □□
 □□□ □□
 □□□ □□ □

17 mm
2 mm
 □□ □□□
1 x 16 - 19 mm

QTMB 18-21


EAN

□□□ □

42517
4251269321610
10
1
 □□(RAL 7035□ □□)
40 mm
39 mm

□□ □□
 □□□ □□
 □□□ □□ □

17 mm
2 mm
 □□ □□□
1 x 18 - 21 mm

QTMB 20-23


EAN

□□□ □

42518
4251269321627
10
1
 □□(RAL 7035□ □□)
40 mm
39 mm

□□ □□
 □□□ □□
 □□□ □□ □

17 mm
2 mm
 □□ □□□
1 x 20 - 23 mm

QTMB 22-25


EAN

□□□ □

42519
4251269322723
10
1
 □□(RAL 7035□ □□)
40 mm
39 mm

□□ □□
 □□□ □□
 □□□ □□ □

17 mm
2 mm
 □□ □□□
1 x 22 - 25 mm

QTMB 24-27


EAN

□□□ □

42520
4251269322730
10
1
 □□(RAL 7035□ □□)
40 mm
39 mm

□□ □□
 □□□ □□
 □□□ □□ □

17 mm
2 mm
 □□ □□□
1 x 24 - 27 mm

QTMB 26-29

EAN

□□□ □

42521
4251269322747
10
1
 □□(RAL 7035□ □□)
40 mm
39 mm

□□ □□
 □□□ □□
 □□□ □□ □

17 mm
2 mm
 □□ □□□
1 x 26 - 29 mm

