

QTMB | QUICK CONNECT (QUICK CONNECT)

Ø 14 - 29 mm / IP54



QTMB QUICK CONNECT fitting.

Ø 14 - 29 mm (Ø 3mm) fitting.

IP54

HL3
EN 45545-2

ECOLAB
certified

UV
ISO 4892-2A

PNEUMATICS

RoHS
compliant

REACH
COMPLIANCE


Made in
Germany

IP (EN 60529)	IP54
	Ø 14 - 29 mm
	UL94-V0, Ø 14 - 17 mm
	-40 C° to 100 C°
	Ø 14 - 29 mm, Ø 3mm

FEATURES

- Quick connection fitting
- Ø 14 - 29 mm fitting
- UL94-V0, Ø 14 - 17 mm
- Ø 14 - 29 mm, Ø 3mm

TECHNICAL DATA




EAN

42545
4251269321634
10
Ø (RAL 7035)
40 mm
39 mm
17 mm

Ø 14 - 29 mm
Ø 3mm

2 mm
1




EAN

Ø 14 - 17 mm

42515
4251269321603
10
1
Ø (RAL 7035)
40 mm
39 mm

Ø 14 - 17 mm
Ø 3mm

17 mm
2 mm
Ø 14 - 17 mm
1 x 14 - 17 mm




EAN

□□□ □

42516
4251269321986
10
1
□□(RAL 7035□ □)
40 mm
39 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

17 mm
2 mm
□□ □□□
16 - 19 mm
1 x 16 - 19 mm




EAN

□□□ □

42517
4251269321610
10
1
□□(RAL 7035□ □)
40 mm
39 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

17 mm
2 mm
□□ □□□
18 - 21 mm
1 x 18 - 21 mm




EAN

□□□ □

42518
4251269321627
10
1
□□(RAL 7035□ □)
40 mm
39 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

17 mm
2 mm
□□ □□□
20 - 23 mm
1 x 20 - 23 mm




EAN

□□□ □

42519
4251269322723
10
1
□□(RAL 7035□ □)
40 mm
39 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

17 mm
2 mm
□□ □□□
22 - 25 mm
1 x 22 - 25 mm




EAN

□□□ □

42520
4251269322730
10
1
□□(RAL 7035□ □)
40 mm
39 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

17 mm
2 mm
□□ □□□
24 - 27 mm
1 x 24 - 27 mm



EAN

□□□ □

42521
4251269322747
10
1
□□(RAL 7035□ □)
40 mm
39 mm

□□ □□
□□□ □□
□□□ □□ □
□□□ □□ □

17 mm
2 mm
□□ □□□
26 - 29 mm
1 x 26 - 29 mm