

Connectorbehuizingen & insertsets 3A / 4A

voor adaptertules AT-HA & kabelinvoerframes MIS



icotek offers 3A or 4A insert sets and matching connector housings with integrated M20 (cable diam. 6 - 12 mm) or M25 (cable diam. 13 - 18 mm) cable glands for [adapter grommets AT-HA](#) and [split cable entry frames MIS](#).

The connector housings are compatible and CE-compliant with numerous insert manufacturers (Harting, Ilme, Phoenix Contact, TE Connectivity, Weidmüller, Lapp, Amphenol, Molex, RS Pro, ...).

EN 45545-2

certified

ISO 4892-2A

IK04

IEC 61984

UL 1977

UL ECBT2

RoHS compliant

REACH COMPLIANCE

Made in Germany

UL

Specificaties

Materiaal	Behuizing: Polyamide Einsatz: Polycarbonaat
Vlam klasse	UL94-V0, zelfdovend
Temperatuur	-40 C° tot 125 C°
Eigenschappen	zonder siliconen, halogeenvrij

Voordelen

Producttypes en maten

Art.nr.	55510
EAN	4251269337499
Aantal	5
Nominale stroom	10 A
Nominale spanning	230 V



Art.nr.	55511
EAN	4251269337
	529
Aantal	5
Nominale stroom	10 A
Nominale spanning	230 V



Art.nr.	55514
EAN	
Aantal	5
Cable gland	M20
Voor kabeldiameter	1 x 6 - 12 mm
s	



Art.nr.	55515
EAN	
Aantal	5
Cable gland	M25
Voor kabeldiameter	1 x 13 - 18 mm
s	

