

# KEL 16-2MT

## Extended cable entry frames



V2A anti-corrosive

Also available with stainless steel screws (V2A).



Also available with threaded bushings.






Configure online now



IP54

1.11

Description	Type	Order No.	Grommets small   large	PU
	KEL 16 24-2MT	42149	24 -	1
	KEL 16 24-2MT with V2A screws	42149.200	24 -	1
	KEL 16 12-2MT	42148	8 4	1
	KEL 16 12-2MT with V2A screws	42148.200	8 4	1
	KEL 16 6-2MT	42147	- 6	1
	KEL 16 6-2MT with V2A screws	42147.200	- 6	1

### Product description

The KEL 16-2MT is our largest frame providing the ability to route and seal up to 96 cables.

The cable entry frames KEL 16-2MT series are KEL 16 frames extended with two additional middle frames for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 96 cables. All frame systems come with a rubber gasket.

### Advantages & benefits

- Maintain manufacturer's warranty on pre-terminated cables
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

### Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
Temperature	-40°C to +140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	126 × 86 mm
Frame depth	17 mm

### Accessories

KT Cable grommets	48 - 52
AT Adapter grommets	54 - 57
KEL-EMC Cable collectors	148 - 150
ST Plugs	53