

KEL 24-2MT

Extended cable entry frames



Configure online now

IP54



V2A anti-corrosive
Also available with stainless steel screws (V2A).



Also available with threaded bushings.

Product description

The KEL 24-2MT is our largest frame providing the ability to route and seal up to 120 cables.

The cable entry frames KEL 24-2MT series are KEL frames extended with two additional middle frames for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 120 cables. All frame systems come with a rubber gasket.

Advantages & benefits











- Maintain manufacturer's warranty on pre-terminated cables
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
Temperature	-40°C to +140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	126 × 112 mm / Page 220-221
Frame depth	17 mm

Accessories

KT Cable grommets	48 - 52
AT Adapter grommets	54 - 57
KEL-EMC Cable collectors	148 - 150
ST Plugs	53

Description	Type	Order No.	Grommets small large	PU
	KEL 24 30-2MT	42234	30 -	1
	KEL 24 30-2MT with V2A screws	42234.200	30 -	1
	KEL 24 27-2MT	42233	26 1	1
	KEL 24 27-2MT with V2A screws	42233.200	26 1	1
	KEL 24 24-2MT	42227	22 2	1
	KEL 24 24-2MT with V2A screws	42227.200	22 2	1
	KEL 24 21-2MT	42226	18 3	1
	KEL 24 21-2MT with V2A screws	42226.200	18 3	1
	KEL 24 12-2MT	42223	6 6	1
	KEL 24 12-2MT with V2A screws	42223.200	6 6	1