

KEL 24-MT

Extended cable entry frames



V2A anti-corrosive













Also available with threaded bushings.



Configure online now



1.11

Description	Type	Order No.	Grommets small large	PU
	KEL 24 20-MT	42232	20 -	1
	KEL 24 20-MT with V2A screws	42232.200	20 -	1
	KEL 24 17-MT	42224	16 1	1
	KEL 24 17-MT with V2A screws	42224.200	16 1	1
	KEL 24 14-MT	42225	12 2	1
	KEL 24 14-MT with V2A screws	42225.200	12 2	1
	KEL 24 11-MT	42222	8 3	1
	KEL 24 11-MT with V2A screws	42222.200	8 3	1
	KEL 24 8-MT	42221	4 4	1
	KEL 24 8-MT with V2A screws	42221.200	4 4	1

Product description

The cable entry frame KEL 24-MT provides additional cable routing possibilities.

The KEL 24-MT series are KEL frames extended with an additional middle frame for routing additional cables. Thus allowing the quick, easy and cost effective routing solution for up to 80 cables.

All frame systems come with a rubber gasket.

Advantages & benefits

- Maintain manufacturer's warranty on pre-terminated cables
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
Temperature Properties	-40°C to +140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	82 × 112 mm / Page 220-221
Frame depth	17 mm

Accessories

KT Cable grommets	48 - 52
AT Adapter grommets	54 - 57
KEL-SNAP Mounting frames	31
KEL-EMC Cable collectors	148 - 150
ST Plugs	53