


# KEL-B

## Cable entry frames



Split KT grommets


**V2A**  
 anti-corrosive



Also available with stainless steel screws (V2A).



Also available with threaded bushings.


**IP54**

1.11

Description	Type	Order No.	Grommets small   large	PU
	KEL-B4	42204	4  -	10
	KEL-B4 with V2A screws	42204.200	4  -	10
	KEL-B1	42206	-	10
	KEL-B1 with V2A screws	42206.200	-	10

### Product description

Centrally split cable entry system for routing cables with connectors, providing an IP54 / up to UL type 12 rating. The slit grommet matching the cable diameter is placed around the cable and inserted into the cable entry frame. Either a cut-out of 36 mm or 46 mm in height can be chosen depending on the cables being routed. The split cable entry frame KEL-B matches exactly the cut-out dimensions of 46 × 46 mm measuring instruments. All frame systems come with a rubber gasket.

### Advantages & benefits

- Maintain manufacturer's warranty on pre-terminated cables
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Space saving shape
- Small cut-out, high cable density
- Strain relief according to EN 62444
- High stability, vibration resistant

### Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of cable grommets (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Temperature	- 40°C to + 140°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	46 × 46 mm / Page 220-221
Frame depth	17 mm

### Accessories

KT Cable grommets	48 - 52
AT Adapter grommets	54 - 57
KEL-SNAP Mounting frames	31
KEL-EMC Cable collectors	148 - 150
FP Flange plates	194 - 203
ST Plugs	53