

# KEL-DPZ-B

## Cable entry plates



Also available in black.



Also available with threaded bushings.



Membrane on front

### Product description

The KEL-DPZ-B entry plates are designed for routing cables without connectors.

The assembly of the KEL-DPZ-B with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane and push the cables through. The KEL-DPZ-B provides strain relief and protection IP66 / UL type 12.

With an area of only 46 × 46 mm, up to 25 cables can be easily routed and sealed.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

### Advantages & benefits




- Space saving shape
- Dual sealing of cables acc. to IP66/UL type 12
- High cable density
- Fast and easy assembly
- Hygienic design

### Specifications

Material	<b>Frame: Polyamide (PA)</b> <b>Sealing plate: Elastomer</b>
Colour	■ grey (similar RAL 7035) ■ black
Flame class	<b>UL94-Vo, self-extinguishing</b>
IP rating	<b>IP66 (certified acc. to EN 60529)</b>
UL type rating	<b>UL type 12 (acc. to UL 50E)</b>
Temperature	<b>- 40°C to + 100°C (static)</b>
Properties	<b>Halogen-free, silicone-free</b>
Cut-out dimensions	<b>46 × 46 mm / page 220 - 221</b>
Plate depth	<b>10 mm</b>

### Accessories

ST-B Plugs	93
FP Flanged plates	194 - 203

Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-B 13	■ 43794 ■ 50794	8 × 3.2 - 6.5 mm 4 × 5 - 10.2 mm 1 × 16 - 22 mm	10
	KEL-DPZ-B 17	■ 43796 ■ 50796	10 × 3.2 - 6.5 mm 4 × 5 - 10.2 mm 2 × 7.5 - 12 mm 1 × 9 - 16.2 mm	10
	KEL-DPZ-B 25	■ 43798 ■ 50798	25 × 3.2 - 6.5 mm	10

\* Only valid for grey product types