


KVT 80

Split cable glands for front mounting



Product description

The KVT 80 split cable glands are designed for routing and sealing cables with connectors. By assembling the two frame halves with the screws provided, the grommets provide sufficient pressure on the routed cables to obtain a high degree of strain relief. The KVT 80 can be fitted to a wall thickness from 1.5 mm to 10 mm. A flat rubber gasket is included in the shipment.

Advantages & benefits

- Insertion of pre-terminated cables
- Maintain manufacturer's warranty on pre-terminated cables
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Fast and easy mounting from the front side
- Strain relief according to EN 62444

Note

When mounting the KVT 80 on sheet metal, we recommend the following torque values:
 1.5 mm sheet = 1 N m | 2 - 10 mm sheet = 1.5 N m


Specifications


Material	Polycarbonate (PC)
Colour	<input type="checkbox"/> grey (similar RAL 7035) <input checked="" type="checkbox"/> black
Flame class	UL94-V0, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Temperature	- 30°C to + 100°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimension	80 mm in diameter


Accessories

Cable grommets	48 - 52
ST Plugs	53

Description	Type	Order No.	Grommets KT small large	PU
-------------	------	-----------	---------------------------	----

	KVT 80 3	<input type="checkbox"/> 45236	2 1	1
		<input checked="" type="checkbox"/> 45239		

	KVT 80 6	<input type="checkbox"/> 45237	6 -	1
		<input checked="" type="checkbox"/> 45238		



*Only valid for grey product types