

PFK|SKL

EMC Shield clamps, pluggable



Secure grip on metal sheets due to mounting claws



| Type | Order No. | Shield diameter | PU |
|------|-----------|-----------------|----|
|------|-----------|-----------------|----|

| PFK SKL - Type A (for wall/sheet thickness 1.5 - 2 mm) | | | |
|--|---------|------------|----|
| PFK-A SKL 1.5-3 | 36778.1 | 1.5 - 3 mm | 10 |
| PFK-A SKL 3-6 | 36778.2 | 3 - 6 mm | 10 |
| PFK-A SKL 6-8 | 36778.3 | 6 - 8 mm | 10 |
| PFK-A SKL 8-11 | 36778.4 | 8 - 11 mm | 10 |
| PFK SKL - Type B (for wall/sheet thickness 2 - 3 mm) | | | |
| PFK-B SKL 1.5-3 | 36782.1 | 1.5 - 3 mm | 10 |
| PFK-B SKL 3-6 | 36782.2 | 3 - 6 mm | 10 |
| PFK-B SKL 6-8 | 36782.3 | 6 - 8 mm | 10 |
| PFK-B SKL 8-11 | 36782.4 | 8 - 11 mm | 10 |

Product description

PFK|SKL shield clamps are easy to use and effective in earthing single cable shields.

PFK|SKL clamps are used where a screw connection is either not possible or wanted. The PFK|SKL is simply clamped on the sheet. The claws provide a secure grip, even in case of vibrations.

Advantages & benefits

- Large contact area
- Simple and tool-free mounting, easy assembly
- Shock and vibration resistant, maintenance free
- The spring design requires no adjustments and will permanently maintain contact to the cable shield

Specifications

Material
SKL-clamp Spring steel, zinc plated
PFK-foot Spring steel

Type A: For wall/sheet thickness 1.5 - 2 mm
Type B: For wall/sheet thickness 2 - 3 mm